

Screw Type	ID partlist	Posizione	Prescribed Torque (inch*pond)	Running Torque (inch*pond)	Locking Torque (inch*pond)
Screw #8-32 UNC-3A 7/8" L	25	UP-LEFT	44 min. to 51 max	10.0	54.0
Screw #8-32 UNC-3A 7/8" L	25	UP-RIGHT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 7/8" L	25	DOWN-LEFT	44 min. to 51 max	8.0	52
Screw #8-32 UNC-3A 7/8" L	25	DOWN-RIGHT	44 min. to 51 max	8.0	52
Screw #8-32 UNC-3A 5/8" L	24	1-UP-LEFT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	2-UP-LEFT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	3-UP-LEFT	44 min. to 51 max	9.0	53.0
Screw #8-32 UNC-3A 5/8" L	24	4-UP-LEFT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	5-UP-LEFT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	1-UP-RIGHT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	2-UP-RIGHT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	3-UP-RIGHT	44 min. to 51 max	7.0	51.0
Screw #8-32 UNC-3A 5/8" L	24	4-UP-RIGHT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	5-UP-RIGHT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	1-DOWN-LEFT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	2-DOWN-LEFT	44 min. to 51 max	9.0	53.0
Screw #8-32 UNC-3A 5/8" L	24	3-DOWN-LEFT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	4-DOWN-LEFT	44 min. to 51 max	9.5	53.5
Screw #8-32 UNC-3A 5/8" L	24	5-DOWN-LEFT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	1-DOWN-RIGHT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	2-DOWN-RIGHT	44 min. to 51 max	8.5	52.5
Screw #8-32 UNC-3A 5/8" L	24	3-DOWN-RIGHT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	4-DOWN-RIGHT	44 min. to 51 max	8.0	52.0
Screw #8-32 UNC-3A 5/8" L	24	5-DOWN-RIGHT	44 min. to 51 max	8.5	52.5

Screw 1 è la prima dal frontale
"LEFT" vista frontale

Dynamometric wrench Tecnoqi s/n 330599 0-30 lb in
calibrated 05/06/08 mod 603
Torque wrench Beta 608/2 s/n 2006/198029 40-180 lb in
calibrated 27/7/06 new

Backplane

UG Crate

Spare

Row 2 16/6/2008

Screw Type	ID partlist	Posizione	Prescribed Torque (inch*ounces)	Running Torque (inch*pound)	Locking Torque (inch*pound)
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-1-UP	65 (4.06)	2.5	6.5
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-1-MIDDLE	65	7.0	5.0
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-1-DOWN	65	2.5	6.5
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-2-UP	65	2.5	8.5
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-2-MIDDLE	65	1.0	5.0
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-2-DOWN	65	3.0	7.0
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-3-UP	65	2.5	6.5
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-3-MIDDLE	65	1.0	5.0
Screw #4-40 UNC-3A 5/8" L	23	STIFF.-3-DOWN	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	1-DOWN	65	2.0	6.0
Screw #4-40 UNC-3A 1/4" L	22	2-DOWN	65	3.0	7.0
Screw #4-40 UNC-3A 1/4" L	22	3-DOWN	65	2.0	6.0
Screw #4-40 UNC-3A 1/4" L	22	4-DOWN	65	2.0	6.0
Screw #4-40 UNC-3A 1/4" L	22	5-DOWN	65	2.0	7.0
Screw #4-40 UNC-3A 1/4" L	22	6-DOWN	65	3.0	7.0
Screw #4-40 UNC-3A 1/4" L	22	7-DOWN	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	8-DOWN	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	1-UP	65	2.0	6.0
Screw #4-40 UNC-3A 1/4" L	22	2-UP	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	3-UP	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	4-UP	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	5-UP	65	2.0	6.0
Screw #4-40 UNC-3A 1/4" L	22	6-UP	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	7-UP	65	2.5	6.5
Screw #4-40 UNC-3A 1/4" L	22	8-UP	65	2.5	6.5

Stiff. 1 è il sinistro vista retro

Screw 22 1 è la prima da sinistra vista retro