Evaluate numerically and plot graphically the convolution integral of the energy spectrum f(E) with a gaussian resolution g(E) defined below.

 $f(E) = f_1(E) + f_2(E) + f_3(E)$

 $f_1(E) = 1/E$ for $0.1 \le E \le 0.9$ MeV $f_1(E) = 0$ for $E \le 0.1$ or $E \ge 0.9$ MeV

 $f_2(E) = G(\mu = 1 \text{ MeV}, \sigma = 0.01 \text{ MeV})$

 $f_3(E) = G(\mu = 1.3 \text{ MeV}, \sigma = 0.01 \text{ MeV})$

g(E)=G(E, σ) with $\sigma/E = 5\%/\sqrt{E(MeV)}$



At the end of the event selection looking for a signal e+e- =>X we get - candidate events: Ncand = 1590; - background events: Nb=640±60 (evaluated from side-bands); The efficiency is $\mathcal{E} = 0.246$ with negligible uncertainty a) Evaluate the number of signal events N_X and its relative uncertainty. b) We want to reduce the uncertainty on the signal and apply a rejection on the background. Assuming an uncertainty of 10% on the background evaluation (after rejection), which rejection factor is needed on Nb above to obtain $\sigma(N_X)/N_X < 3.5\%$?

Given the formula:

$$\frac{\left|\eta_{+-}\right|^{2}}{\left|\eta_{00}\right|^{2}} = \frac{\left[\frac{BR\left(K_{L} \to \pi^{+}\pi^{-}\right)}{BR\left(K_{S} \to \pi^{+}\pi^{-}\right)}\right]}{\left[\frac{BR\left(K_{L} \to \pi^{0}\pi^{0}\right)}{BR\left(K_{S} \to \pi^{0}\pi^{0}\right)}\right]} \approx 1 + 6\Re e\left(\frac{\varepsilon'}{\varepsilon}\right)$$

Show that :

$$\delta \Re e \left(\frac{\varepsilon'}{\varepsilon}\right)_{stat} = \frac{1}{6} \frac{1}{\sqrt{(2/3)N_L^0}}$$

with N_{L}^{0} number of counts $K_{L}^{-} \ge \pi^{0} \pi^{0}$.

1) In which approximation does the formula hold?

The relationship between branching ratios BR_{S.L} and counts N_{S.L} is given by:

$$N_{S,L}^{\pm,0} = N_{S,L}^{\pm,0}(obs) - Bck_{S,L}^{\pm,0} = N_{KK} \cdot \rho_{S,L}(tag) \cdot BR_{S,L}^{\pm,0} \cdot \langle \rho_{S,L}^{\pm,0} \rangle \cdot \iint_{FV} g(l-l')I(l) dl dl'$$

th:

with:

 $- N_{s,L}^{\pm,0}(obs) \text{ is the number of observed decays into } \pi^{+}\pi^{-}, \pi^{0}\pi^{0}$ $- N_{KK} \text{ is the total number of produced } K_{s}K_{I} \text{ pairs}$ $- \rho_{s,L}(tag) \text{ is the tagging efficiency}$ $- BR_{s,L}^{\pm,0} \text{ is the branching ratio of the decay } K_{s,L} => \pi^{+}\pi^{-}, \pi^{0}\pi^{0}$ $- \langle \rho_{s,L}^{\pm,0} \rangle \text{ is the average detection efficiency for the decays } K_{s,L} => \pi^{+}\pi^{-}, \pi^{0}\pi^{0}$ $- \iint_{FV} g(l-l')I(l)dldl' \text{ is the convolution integral of an exponential decay intensity}$ $I(l) = \exp(-l/l_{s,L}) \text{ with the resolution } g(l-l') \text{ on the decay length}$ I, and integrated on the fiducial volume FV

- $Bck_{s,L}^{\pm,0}$ is the contribution of background events

$$N_{L}^{0} = \underbrace{\frac{3}{\mu b}}_{\sigma_{e^{+}e^{-} \rightarrow \phi}} \cdot \underbrace{\underbrace{\mathcal{L}}_{\int Ldt}}_{\int Ldt} \cdot \underbrace{\underbrace{0.66}_{\rho_{L}(tag)}}_{BR(\phi \rightarrow K_{S}K_{L})} \cdot \underbrace{\underbrace{10^{-3}}_{BR_{L}^{0}} \cdot \underbrace{\left(e^{-3q/350} - e^{-15q/350}\right)}_{fiducial volume}$$

2) Given an integrated luminosity of $\mathcal{L}=10^4$ pb⁻¹, which rejection factor of the background $K_L > 3\pi^0$ (on the signal $K_L > 2\pi^0$) is necessary to have an uncertainty $\delta(\text{Re}(\epsilon'/\epsilon)) < 3x10^{-4}$ and assuming to know the background with a 20% precision?